

Monsoon Commercial UMD Mixed Flow Fans

- High performance and fully speed controllable
- Motor attached to fan body by two quick release clips for maintenance
- Two speed motor with option of overrun timer (2 to 30 minutes)
- Motor equipped with Standard Thermal Overload Protection (STOP), IPX4
- Working temperature of up to 60°, supply voltage 220-240v 50Hz



CODE	DESCRIPTION
UMD200	200mm Standard In-Line Fan (1,040m ³ /h)
UMD200T	200mm Timer In-Line Fan (1,040m ³ /h)
UMD250	250mm Standard In-Line Fan (1,400m ³ /h)
UMD250T	250mm Timer In-Line Fan (1,400m ³ /h)
UMD315	315mm Standard In-Line Fan (2,350m ³ /h)
UMD315T	315mm Timer In-Line Fan (2,350m ³ /h)

Please see page28 for smaller models.

Metal Cased External Centrifugal Fans

- For outdoor wall installation
- Removes noise from in the building
- Ball bearing motor, IPX4 thermal protection
- Speed controllable, low noise levels



CODE	DESCRIPTION
UEC100	100mm External Centrifugal Fan (280m ³ /h)
UEC125	125mm External Centrifugal Fan (390m ³ /h)
UEC150	150mm External Centrifugal Fan (600m ³ /h)