


Performance Chart



Acoustic Information

	83	125	250	200	*	×	¥	⋇	Total	dBA@3⊓
Inlet	72	70	60	56	49	46	39	33	74	38
Outlet	79	69	66	75	64	63	53	45	81	53
Breakout	63	57	59	64	57	56	46	36	68	43

Sound Power Level Spectra dB (re 10⁻¹² Watts)

For ducted units, sound power is given as In Duct with end reflections added. Stated dB(A) levels at 3m with spherical propagation at a reference level of 2 x 10 $^{-1}$ Pa



405215

Tech Ref File:

Stock Reference: 40521

Product Description: Sentinel Kinetic Advance
Product Type Ventilation

Product Range: Heat Recovery
Impeller: Backward Curved

Casing: ABS
Speed: Variable
Airstream Temperature: -20°C to 45°C

dBA: 43
Specific Fan Power & dB(A) shown are at duty point.

Warranty: Up to 5 years

Electrical Information

Watts 190

Supply Voltage: 220-240V/1/50Hz

Motor IP Rating: IP22
S.T.O.P. Protection: Yes
Speed Controllable: In Built


Optional Accessories

Part No

Description



Dimensions



Dimensions shown in mm Weights in kg

SAP Appendix Q 2012

		Thermal Efficiency (%)	SFP (W/l/s)
	K+1	93	0.39
	K+2	92	0.46
	K+3	91	0.55
	K+4	91	0.7
	K+5	90	0.85
	K+6	89	1.07
	K+7	89	1.31