

Airflow iCON - The Versatile Fan

Select the fan, choose your choice of control module. Its iCON simple.

AIRFLOW iCON™ 15

iCON 15 is ideal for toilets, en-suites, shower rooms and small bathrooms. Recessed into the wall or ceiling, it is stylish and unobtrusive, even in the smallest space. Available in White, Sandstone, Silver, Anthracite and Chrome



Fan Size	Ductable	Power	Voltage	Air flow
197x40mm	Short Runs	14.5W	230V	21 l/sec (76m³/hr)

AIRFLOW iCON™ 30

iCON 30 is quiet, powerful and designed for recessed or surface mounting in walls or ceilings in larger toilets, bathrooms and utility rooms. Available in White, Sandstone, Silver and Anthracite



Fan Size	Ductable	Power	Voltage	Air flow
225x43mm	Longer Runs	30W	230V	32 l/sec (118m³/hr)

AIRFLOW iCON™ 60

iCON 60 is the largest fan in the range, suitable for recessed or surface mounting in walls or ceilings and is highly efficient in domestic kitchens and residents' lounges. Available in White, Silver and Anthracite



Fan Size	Ductable	Power	Voltage	Air flow
280x55mm	Longer Runs	75W	230V	72 l/sec (260m³/hr)

Choose your control module

- Pull Cord
- Timer
- Humidity, Pull Cord, Timer
- PIR, Timer
- Two Speed, Trickle/Boost
- PIR, Humidity, Timer



Select the fan, choose the control module - All modules fit all fans

Accessories

iCON 15 and iCON 30 can be ducted through standard 100mm (4") rigid, flexible or flat ducting. iCON 60 can discharge through 150mm (6") ducting, Airflow supply a comprehensive range of ducting accessories and controllers to complement an installation.



High rise cowl kit



TECHNICAL SPECIFICATION			
MODEL	iCON 15	iCON 30	iCON 60
Part No.	72591501	72591601	72591701
Extract volume	21 l/sec (76 M³/hr)	32 l/sec (118 M³/hr)	72 l/sec (260 M³/hr)
Sound pressure dB(A) @ 3m	35	34.5	44.5
Impeller	Axial	Mixed centrifugal/axial	Mixed centrifugal/axial
Mounting (Wall/Ceiling)	Recessed	Recessed and surface	Recessed and surface
Weight (Kg)	0.74	1.11	1.97
Ductable	Up to 4m	Up to 9m	Up to 9m
Outlet (dia)	100mm (4")	100mm (4")	150mm (6")
Power (watts)	14.5W	30W	75W
Voltage	230V/1PH/50Hz	230V/1PH/50Hz	230V/1PH/50Hz
Max Amb Temp	40°C	40°C	40°C
IP Rating	□, △, IPX4	□, △, IPX4	□, △, IPX4

AVAILABLE NOW FROM

i-sells.co.uk



Showroom:
15 St John's Parade
Sidcup High Street
DA14 6ES


EMAIL: sales@i-sells.co.uk
SALES: 020 8463 9696
WEB: www.i-sells.co.uk

AIRFLOW™



ADF IC000/0611

AIRFLOW
iCON™
The stylish face of ventilation



CHROME



reddot design award

AIRFLOW™

A stylish, slim and unobtrusive range of fans for toilet, bathroom and kitchens with a unique iris shutter and a choice of colours too!

AIRFLOW iCON™

The stylish face of ventilation

Style supplied as standard.

iCON style fans complement modern day living by harmonising with virtually any interior design. Neat, unobtrusive and stylish, they provide quiet and reliable ventilation while blending into the background.

Available from stock in Anthracite, Sandstone, Silver, Glacier White and Chrome (iCON 15 only) matt wipe-clean finish, they add colour and co-ordination to your toilet, bathroom and kitchen – and at surprisingly low cost.

“A round fan for a round hole”

The choice of three aesthetically designed fans in the iCON range means you can fit the perfect size for the size of room and the application. The low profile iCON 15 axial fan is sleek and slim. The iCON 30 and iCON 60 mixed centrifugal/axial flow fan technology makes them not only highly compact and efficient but also extremely quiet in operation and suitable for use with ducting.



- **Stylish, slim & unobtrusive in walls and ceilings**
- **Unique iris shutter, prevents back draughts, operates silently and helps reduce noise ingress**
- **Interchangeable control modules match fan to your requirements**
- **Complies with latest Building Regulations**
- **12V DC low energy, low watt, long life/SELV versions**
- **Splashproof, tiling friendly, wipe clean cover**
- **Comprehensive range of accessories**
- **Three year 'no quibble' guarantee**



Simple to Install

The twist on/off cover uses only a single side entry fixing screw. Cantilever fixing lugs enable recessed installation on uneven surfaces. iCON 30 and iCON 60 are also supplied with a narrow contour skirt for surface mounting if preferred.

The ‘snap-in’ module is quick to fit and wire. Tiling is a breeze with the circular cover flange, reducing the need to ‘make good’ and one wipe and the cover is clean.

iCON 15 and iCON 30 can be ducted through standard 100mm (4") rigid, flexible or flat ducting. iCON 60 can discharge through 150mm (6") ducting. Airflow supply a comprehensive range of ducting, accessories and controllers to complement an installation.



CEILING INSTALLATION



RECESSED INSTALLATION



SURFACE MOUNTED

Low energy SELV fans

iCON 15 and iCON 30 are available in low watt safety extra low voltage versions with 12V DC motors for significant energy savings. Contact Airflow for details



Toilets and bathrooms

With efficient extraction in a range of capacities, iCON fans are ideally suited to toilets, en suites and bathrooms.



Kitchens and utility rooms

iCON's design fits unobtrusively into any style of kitchen and perfect for utility rooms.



Safety and Economy

Low energy, low watt iCON fans (12V DC) provide long life combined with SELV (safety extra low voltage) protection in wet zones.